


NEW



Lowara ecocirc[®] BASIC and ecocirc[®] PREMIUM

THE NEW HIGHLY EFFICIENT CIRCULATORS WITH THE
PATENTED ANTI-BLOCK-TECHNOLOGY

 **LOWARA**
a xylem brand

How can efficiency even v

The simple spherical motor design....

Impressively simple, that's the shaftless spherical motor design. It requires only one single bearing, which is even self re-aligning but does not require any shaft at all. That significantly reduces the number of costly and complicated parts.



ErP
ready
2015

Tomorrow's high efficiency ready now: the new Lowara ecocirc® are compliant with the ErP-Directive for 2015

ecocirc



PLUS X AWARD®

achieved for:

Innovation
High Quality
Functionality



PLUS X AWARD®

honored as:

BEST PRODUCT
OF THE YEAR
2013

work harder?

...with the patented Anti-Block-Technology!



The spherical rotor

With the evolutionary Anti-Block-Technology, the ceramic bearing ball is now encapsulated inside in the centre of the rotor/impeller unit.

The new design

Magnetite and sudge, which are both found in the pumped liquid are both magnetic, this can accumulate at the permanent magnetic parts of a high efficiency pump, and therefore block and damage it, or decrease the pump's efficiency. Our new Anti-Block-Technology separates the main flow of the pumped media completely from the permanent magnetic parts, blocking up even in very old, open systems is impossible by our pump design.



Dry-run protection and enhanced motor technology







Ecocirc circulators come standard with an internal temperature sensor which measures the temperature directly at electronic components. Electronic temperature from 105°C to 115°C makes the pump reduce its speed continuously. The pump stops automatically at 125°C, and restarts again after cooling down at 115°C.

In addition, the inrush-current limitation of 6,5 Amp protects also older external heating controls that may be installed on site.

Easy settings

One single knob serves all needs: stepless control options, automatic air purge and maximum hydraulic performance. The multi-colour LED inside the transparent knob indicates the currently chosen control option:

Control options:

-   white: stepless fixed speed, especially for boiler feed, single-pipe heating systems, systems with hydraulic separators;
-   blue: automatic proportional pressure control $\Delta p-v$, especially for thermostatic radiator valves
-   green: automatic constant pressure control $\Delta p-c$, especially for underfloor heatings (available only in PREMIUM models)

In addition, a blink code of the LED indicates about potential messages.

Automatic air purge:

Simply turn the knob towards the air purge symbol for more than 5 seconds. This will start the automatic air purging, no matter which control option had been chosen before. This will effectively remove the air from the inner of the pump. The circulator will return automatically to all it's previously chosen settings after having finished this service mode.

Quick connection

ecocirc BASIC and ecocirc PREMIUM: plug, no tools required for assembly



Affordable efficiency!

Approximately 10 to 15 percent of the electricity consumption of an average household is caused by domestic heating circulators. The overwhelming majority of these consist of fixed three speed standard circulators. The EU's new Eco-Design Directive, the ErP-Directive EC 641/2009 has started 1st January 2013. The purpose is to reduce the energy consumption significantly. Again in 2015 these strict requirements will be tightened further.

To date there was only the choice of purchasing an inexpensive inefficient standard circulator with high energy consumption or selecting a modern high efficiency pump which was quite costly but very energy saving. The new Lowara ecocirc made by Xylem strikes the balance between these two options: a modern, electronically controlled high efficiency pump, which pays for itself within a short period of installation.

Xylem now offers two options, both focus on a quick payback time: the Lowara ecocirc, a highly efficient circulator, and also the ecocirc PREMIUM, which offers in addition a multi-display, a plug for a quick and easy installation and even one more control option.

ecocirc[®] BASIC

The Lowara ecocirc BASIC focuses on quick amortisation and short payback times. No compromise in reliability and high efficiency, all with a clear focus on the essentials in mind.



Two stepless control options


- stepless fixed speed
- automatic proportional pressure control $\Delta p-v$



The Lowara ecocirc BASIC circulator has won the Plus X "**Best Product of the Year 2013**" award.

The Plus X Awards is the world's largest innovation award ceremony for technology, sport and lifestyle products, and honors manufacturers of unique, innovative high-quality products. The winners of Plus X Awards are chosen by an independent, international panel of 25 judges from various industries.

In addition, it also was awarded as best in class for Innovation, High Quality and Functionality.



* Every household and every heating habit differ. The facts above are based on a standard one family home with 3 inhabitants in Germany, electricity costs of 20 Cent / kWh, all according to the independent testing institute „Stiftung Warentest“ published 9/2007, page 76ff.

ecocirc® PREMIUM

All Lowara ecocirc PREMIUM come standard with three control options, a plug that does not require a tool for assembly, and even a multi-display mounted on the end cap:



Multi-Display

The automatically alternating display shows either the currently consumed power, the pump head or the flow rate.



Three stepless control options

- stepless fixed speed
- automatic proportional pressure control $\Delta p-v$
- automatic constant pressure control $\Delta p-c$




Plug, no tools required for assembly

An easy and quick electrical connection. The female plug is compatible also with male plugs from previously on site installed third-party circulators.

By turning the stator via the screw ring, the plug can be fixed in any position, making an installation even in the hardest and tightest environment easy.



Product range



Highly efficient circulators for domestic heating Lowara ecocirc BASIC

High efficiency pumps with ECM-technology and permanent magnet rotor for applications like radiant heating (one- and two pipe systems), underfloor and surface heating, boiler feed, solar stations and similar applications; shaftless, maintenance-free spherical motor, magnetite resistant Anti-Block-Technology, switchable control options (step-less manually or automatic variable differential pressure), cathaphoresis coated cast iron pump housing, LED operation indicator, initial current limitations, automatic air purge mode;

| P/N | Description | Version | Pump Housing length (mm) | Connection | For union fittings | EEl | Electric connections | Control options | Magnetite resistance | | | |
|-----------|------------------------|---------|--------------------------|------------|--------------------|---------|----------------------|---|-----------------------|------|---|-----------------------|
| 605008312 | ecocirc BASIC 25-4/180 | 4 meter | 180 | G 1 1/2" | 1" | ≤ 0,21 | plug | - stepless fixed speed - automatic proportional pressure control | Anti-Block Technology | | | |
| 605008411 | ecocirc BASIC 32-4/180 | | | G 2" | 1 1/4" | ≤ 0,21 | | | | | | |
| 605008006 | ecocirc BASIC 15-4/130 | | 130 | G 1" | 1/2" | ≤ 0,22 | | | | | | |
| 605008106 | ecocirc BASIC 20-4/130 | | | G 1 1/4" | 3/4" | ≤ 0,21 | | | | | | |
| 605008209 | ecocirc BASIC 25-4/130 | | | G 1 1/2" | 1" | ≤ 0,21 | | | | | | |
| 605008362 | ecocirc BASIC 25-6/180 | 6 meter | 180 | G 1 1/2" | 1" | ≤ 0,23 | | | | plug | - stepless fixed speed - automatic proportional pressure control | Anti-Block Technology |
| 605008461 | ecocirc BASIC 32-6/180 | | | G 2" | 1 1/4" | ≤ 0,23 | | | | | | |
| 605008056 | ecocirc BASIC 15-6/130 | | 130 | G 1" | 1/2" | ≤ 0,26* | | | | | | |
| 605008156 | ecocirc BASIC 20-6/130 | | | G 1 1/4" | 3/4" | ≤ 0,23 | | | | | | |
| 605008263 | ecocirc BASIC 25-6/130 | | | G 1 1/2" | 1" | ≤ 0,23 | | | | | | |

*ErP ready 2013



Highly efficient circulators for domestic heating Lowara ecocirc PREMIUM

Like ecocirc, however in addition with Multi-Display to show power consumption, pump head and flow rate; automatic constant pressure control Δp -c suitable especially for underfloor heating, plug;

| P/N | Description | Version | Pump Housing length (mm) | Connection | For union fittings | EEl | Electric connections | Control options | Magnetite resistance | | | |
|-----------|--------------------------|---------|--------------------------|------------|--------------------|---------|----------------------|--|-----------------------|------|--|-----------------------|
| 605008311 | ecocirc PREMIUM 25-4/180 | 4 meter | 180 | G 1 1/2" | 1" | ≤ 0,21 | plug | - stepless fixed speed - automatic proportional pressure control - automatic constant pressure control | Anti-Block Technology | | | |
| 605008410 | ecocirc PREMIUM 32-4/180 | | | G 2" | 1 1/4" | ≤ 0,21 | | | | | | |
| 605008005 | ecocirc PREMIUM 15-4/130 | | 130 | G 1" | 1/2" | ≤ 0,22 | | | | | | |
| 605008208 | ecocirc PREMIUM 25-4/130 | | | G 1 1/4" | 3/4" | ≤ 0,21 | | | | | | |
| 605008105 | ecocirc PREMIUM 20-4/130 | | | G 1 1/2" | 1" | ≤ 0,21 | | | | | | |
| 605008361 | ecocirc PREMIUM 25-6/180 | 6 meter | 180 | G 1 1/2" | 1" | ≤ 0,23 | | | | plug | - stepless fixed speed - automatic proportional pressure control - automatic constant pressure control | Anti-Block Technology |
| 605008460 | ecocirc PREMIUM 32-6/180 | | | G 2" | 1 1/4" | ≤ 0,23 | | | | | | |
| 605008055 | ecocirc PREMIUM 15-6/130 | | 130 | G 1" | 1/2" | ≤ 0,26* | | | | | | |
| 605008155 | ecocirc PREMIUM 20-6/130 | | | G 1 1/4" | 3/4" | ≤ 0,23 | | | | | | |
| 605008262 | ecocirc PREMIUM 25-6/130 | | | G 1 1/2" | 1" | ≤ 0,23 | | | | | | |

*ErP ready 2013

Technical Data

| | |
|------------------------|---|
| Motor design | Electronically commutated, shaftless spherical motor design with permanent magnetic rotor |
| Max. system pressure | 10 bar |
| Electric connection | 200 - 240 Volt, 50 / 60 Hertz |
| Power consumption | ecocirc xx-4: 4 - 23 Watt ecocirc xx-6: 4 - 42 Watt |
| Accepted liquids | Heating water VDI 2035 Water/Glycol mixtures* Anti-Block-Technology |
| Magnetite resistance | Accepted |
| temperature range | -10 °C** to +110° C |
| Energy efficiency | ErP 2015 ready |
| Motor protection class | IP 44 |
| Insulation class | F |

* check hydraulic performance with more than 20 % glycol
**non-freezing

Model designation

Connection in DN Pump head in meter




ecocirc PREMIUM 25 - 4 / 180

Model Pump housing length (in mm)




Replacement tool online:
www.lowara.com


Pump curves

-  stepless fixed speed, especially for boiler feed, single-pipe heating systems, systems with hydraulic switch
-  automatic proportional pressure control $\Delta p-v$, especially for radiator heating
-  automatic constant pressure control $\Delta p-c$, especially for underfloor heating (available only in PREMIUM models)


Lowara ecocirc and ecocirc PREMIUM - 4-Meter-Versions



Lowara ecocirc and ecocirc PREMIUM - 6-Meter-Versions



Dimensional drawings



| Models | A in mm | B in inch | C in mm | D in mm | E in mm |
|------------------|------------|--------------|------------|------------|------------|
| ecocirc 25-x/180 | 180 | G 1 1/2 | 104 | 141 | 113 |
| ecocirc 32-x/180 | 180 | G 2 | 104 | 141 | 113 |
| ecocirc 15-x/130 | 130 | G 1 | 104 | 141 | 113 |
| ecocirc 20-x/130 | 130 | G 1 1/4 | 104 | 141 | 113 |
| ecocirc 25-x/130 | 130 | G 1 1/2 | 104 | 141 | 113 |

Xylem |'zīləm|

- 1) The tissue in plants that brings water upward from the roots;
- 2) a leading global water technology company.

We're approximately 12,900 people unified in a common purpose: creating innovative solutions to meet our world's water needs. Developing new technologies that will improve the way water is used, conserved, and reused in the future is central to our work. We move, treat, analyze, and return water to the environment, and we help people use water efficiently, in their homes, buildings, factories and farms. In more than 150 countries, we have strong, long-standing relationships with customers who know us for our powerful combination of leading product brands and applications expertise, backed by a legacy of innovation.

For more information on how Xylem can help you, go to xyleminc.com.



Legal head office
Xylem Water Solutions Italia Srl

Via Gioacchino Rossini 1/A
20020 - Lainate (MI) - Italy
Tel. (+39) 02 90358.1
Fax (+39) 02 9019990
www.xylemwatersolutions.com

For information and technical support
Xylem Service Italia Srl

Via Dottor Vittorio Lombardi 14
36075 - Montecchio Maggiore (VI) - Italy
Tel. (+39) 0444 707111
Fax (+39) 0444 491043
www.lowara.com

Xylem Water Solutions Italia Srl reserves the right to make modification without prior notice.
Lowara, Xylem are trademarks of Xylem Inc. or one of its subsidiaries.
© 2014 Xylem, Inc.

cod. 191007381 - P02/14